


# COUNTERTOP Point-of-Sale



# NX1200

## True Cost Savings

The NEXGO NX1200 countertop payment solution offers secure and reliable transactions, easy software upgrades, and simple configuration to adapt to all business environments resulting in a low cost of ownership.

- **SECURE**  
Supports latest industry standards
- **FUTURE-PROOF**  
EMV & NFC support
- **EXPANDABLE**  
Ethernet and Dial with optional WiFi




## CERTIFICATIONS



[www.nexgo.us](http://www.nexgo.us)

# NX1200



## Features & Benefits

**Security** - Built-in security transaction engine for the highest level of secure payment processing.

**NFC Support** - Improves customer experience by offering support for mobile wallet applications. Certified for both PayPass and PayWave.

**EMV Support** - NEXGO has embraced future-proof strategies, such as EMV, to give you confidence and trust with every transaction.

**Performance** - NEXGO's multi-application platform allows for easy integration with other value-added applications, all in one device.

**Design** - A low-cost terminal featuring a large sized paper roll.

## Terminal Access Portal (TAP)

NEXGO's Terminal Access Portal (TAP) provides the fastest, most secure and truly cost-effective remote device management tool for a wide range of users. Featuring a user-friendly interface, TAP can be accessed anytime, anywhere, ensuring real-time device management.

## Specifications

<b>Processor</b>	ARM9, 32-bit secure processor
<b>Memory</b>	128 MB Flash, 64 MB SDRAM
<b>Slots</b>	2 PSAM card slots 1 additional card slot (optional)
<b>Card Readers</b>	Contactless - ISO/IEC 14443 Magstripe - 3 track, bi-directional Smart card - ISO 7816
<b>Display</b>	128 x 64 monochrome screen, adjustable backlight
<b>Keypad</b>	10 operational keys, 2 functional keys
<b>Audio</b>	Buzzer
<b>Thermal Printer</b>	Paper roll W x D = 58mm x 45mm
<b>Ports</b>	1 USB host 1 Mini USB slave 1 RS232 (PIN pad) 1 Serial 1 LAN 1 PSTN
<b>PIN Pad</b>	Internal or External (G101), 3DES encryption, DUKPT key management
<b>Communication</b>	Ethernet and Dial, WiFi (optional)
<b>Size</b>	L x W x H = 230 x 97 x 75mm
<b>Weight</b>	500g
<b>Environment</b>	Operating temperature: 0°C to 50°C (32°F to 122°F); humidity (non-condense) 10% to 90%; storage temperature: -20°C to 60°C (-4°F to 140°F); humidity (non-condense) 5% to 95%
<b>Power Supply</b>	Input: 100-240V, 50-60Hz Output: 9.5V/2.5A
<b>Certifications</b>	PCI PTS 3.x, PA-DSS 3.x, Paywave, Paypass, EMV Level 1 & 2

